



CONCRETE CRUSHERS			HCC-1V	HCC-2V	HCC-3V	HCC-6V*	HCC-12V*	HCC-16V*
	Excavator class ¹	t	1.5 - 3.0	2 - 4	4 - 7	5 - 10	10 - 17	16 - 21
	Weight	kg	180	250	300	610	1230	1620
	Jaw opening	mm	240	280	358	480	685	610
	Cutter length	mm	84	90	140	140	140	180
	Working pressure	bar	220	250	250	280	350	350
	Oilflow	l/min	20 - 25	40 - 60	60 - 80	80 - 150	150 - 250	180 - 250
	Working pressure rotation	bar	220	120	120	120	140	140
	Oilflow rotation	l/min	8	5	5	10	10	10
	Open/close	sec.	1.3 / 1.6	1.1 / 1.3	1.2 / 1.2	0.8 / 1.4	0.9 / 1.7	0.9 / 1.6

CONCRETE CRUSHERS			HCC-19V*	HCC-24V*	HCC-32V*	HCC-42V*	HCC-58V*	HCC-72V*
	Excavator class ¹	t	20 - 25	22 - 30	29 - 38	36 - 52	50 - 68	66 - 88
	Weight	kg	1960	2380	2960	3920	5440	7140
	Jaw opening	mm	820	890	1090	1370	1500	1680
	Cutter length	mm	180	180	220	260	325	325
	Working pressure	bar	350	350	350	350	350	350
	Oilflow	l/min	180 - 250	200 - 300	250 - 350	300 - 400	350 - 450	400 - 500
	Working pressure rotation	bar	140	140	140	140	140	140
	Oilflow rotation	l/min	10	10	10	10	30	30
	Open/close	sec.	1.7 / 3.3	1.8 / 3.4	2.0 / 2.6	3.5 / 3.1	3.6 / 3.9	3.8 / 4.1

CONCRETE CRUSHERS			HCC-95V*	HCC-110V	HCC-130V	HCC-150V	HCC-320V
	Excavator class ¹	t	85 - 105	90 - 130	94 - 150	100 - 200	200 - 300
	Weight	kg	9380	11940	13850	15800	32000
	Jaw opening	mm	1830	2050	2305	2836	3100
	Cutter length	mm	325	400	400	-	-
	Working pressure	bar	350	350	350	350	350
	Oilflow	l/min	450 - 650	500 - 800	500 - 800	600 - 1000	1000 - 1300
	Working pressure rotation	bar	140	140	140	140	250
	Oilflow rotation	l/min	50	50	50	50	50
	Open/close	sec.	3.8 / 3.9	3.7 / 4.0	3.7 / 4.1	3.8 / 4.3	4.9 / 6.1

¹ Recommended excavator / attachment combination
 * Equipped with replaceable teeth

