



HFP SERIES








Fixed pulverizers








The Hydraram HFP-Pulverizer is specially designed for the secondary demolition of buildings and recycling. The shape of the jaws of the crusher is designed to pick up and crush concrete as effectively as possible. The steel cutters in the back of the pulverizers' jaw can cut reinforcement steel easily. Interchangeable teeth are standard on all models.

This tool is made the most most durable steel HARDOX-400® with an extremely high wear resistance, resulting in minimum maintenance and a long lifespan.

The installed speed valve ensures quick work cycles and immediate results.



FIXED PULVERIZERS			HFP-4V	HFP-7V	HFP-15V	HFP-22
 Excavator class ¹	t		4 - 7	6 - 10	13 - 19	18 - 28
 Weight	kg		460	740	1420	2180
 Jaw opening	mm		-	475	690	810
 Cutter length	mm		-	140	220	260
 Working pressure	bar		-	280	350	350
 Oilflow	l/min		-	40 - 60	120 - 200	200 - 300
 Open/close	sec.		-	3.4 / 5.3	2.0 / 2.6	2.0 / 2.7

FIXED PULVERIZERS			HFP-28V	HFP-35V	HFP-48V	HFP-72V
 Excavator class ¹	t		25 - 35	33 - 45	42 - 68	65 - 85
 Weight	kg		2820	3420	4760	6980
 Jaw opening	mm		870	950	1100	1250
 Cutter length	mm		260	260	300	325
 Working pressure	bar		350	350	350	350
 Oilflow	l/min		250 - 350	300 - 400	350 - 500	450 - 600
 Open/close	sec.		3.0 / 3.2	2.8 / 2.7	2.6 / 2.9	3.0 / 3.7

¹ Recommended excavator / attachment combination

